



CP 066

Fade-out thinner

CP 066 is a specialized thinner designed for blending two-component products, dedicated for both two-coat and single-coat bodywork methods. Its application is particularly effective for creating a blending effect (partial painting of the vehicle) with **ACRYL** pigment paint or clearcoat.

Best suited for precision work, **CP 066** excels in painting small areas, making it ideal for intricate applications like "smart" repairs. This product is available in practical 1-Litre tins, providing a convenient solution for precision painting needs.

PACKAGING	
Volume	Collective packaging
1 l	6 pcs.



EFFICIENT



FOR 2K PRODUCTS



SPRAY VISCOSITY

11-12 sec. DIN Flow Cup 4 mm



RECOMMENDED SIZES FOR PAINT STRAINER

190 µm



POT LIFE

Ready-to-use product



MINIMUM SHELF LIFE

24 months in originally sealed packaging



SUBSTRATE PREPARATION

The transition area is abraded with **P1500-P2000** grade paper or grey fleece with matting paste. Degrease the surface with silicone remover



MIXING RATIO

70 parts of CP 066
30 parts of 2K product



SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**



APPLICATION

One coat is applied in several centimetre-long strips. The best effect is achieved with a small admixture of topcoat. It needs polishing after drying



EVAPORATION TIME AFTER APPLICATION

~4 min after coating at **20°C** and **65%** relative humidity



DRYING

Drying times at **20°C** and **65%** relative humidity: **~10-20 min**